



Technical Specifications

PARTS	THICKNESS H≤1700	RAW MATERIAL	THICKNESS H≥1800	PAINT	
Carcass	1.50 mm	Galvanized Sheet Metal	2.00 mm	RAL7035W Electrostatic Powder Coating	
Front Door	2.00 mm	Sheet Metal (CCRS6112)	2.00 mm	GASKET	
Back Door	1.20 mm	Sheet Metal (CCRS6112)	1.50 mm	Poliuretan Liquid Gasket	
Side Cover	1.20 mm	Sheet Metal (CCRS6112)	1.50 mm	PROTECTION	
Top Cover	1.20 mm	Sheet Metal (CCRS6112)	1.50 mm	IP41 - IK10	
Bottom Cover	1.50 mm	Galvanized Sheet Metal	1.50 mm	AVAILABLE DIMENSIONS	
Mounting Profile	2.00 mm	Galvanized Sheet Metal	2.00 mm	Width: 400-800 mm Height: 1400-2100 mm Depth: 400-800 mm	
Base Corner	2.00 mm	Sheet Metal (CCRS6112)	2.00 mm	*Height dimensions includes 100 mm Floorbase (H+H1)	
Base Cover	1.20 mm	Sheet Metal (CCRS6112)	1.20 mm	DOOR	
Mounting Plate	2.00 mm	Galvanized Sheet Metal	2.00 mm	Front Door: Rod Latch Lock Systems and Concealed Hinge (Front Door can be open up to 110°)	
Code System : EXP: SET-D-FI ⁶²⁰⁴				Main code of Free Standing Modular Type Panels IP41	
SET - D - FI					
"6"					Dimension of Width in "DECIMETER"
"20"					Dimension of Height in "DECIMETER"
"4"				Dimension of Depth in "DECIMETER"	

